













ACCESORIO "CONEX" DE LATÓN

* Idóneo para energía solar por tener los mismos coeficientes de dilatación que el cobre.

MEDIDA	12 mm	15 mm	18 mm	22 mm	28 mm	35mm	42 mm	54 mm
 CODO	2,62	1,77	3,04	3,25	6,34	11,89	18,18	28,67
 TE	4,10	2,54	4,27	4,42	9,45	19,32	28,18	51,43
 TE REDUCIDA	---	4,78	6,87	9,28	10,53	19,30	32,90	98,47
 MANGUITO	2,15	1,63	2,81	3,40	5,35	9,80	14,16	24,66
 OVALILLO	0,35	0,41	0,49	0,49	0,71	1,15	1,73	2,54
 CASQUILLO REDUCCIÓN	1,71	1,88	2,59	2,18	2,83	5,59	10,20	16,43
 TUERCA	0,45	0,57	0,67	0,74	1,15	4,07	4,79	8,21

MEDIDA	 CODO-H	 TE-H	 ENTRONQUE	 RACOR	 PLACA
12 - 3/8	---	---	2,33	2,46	---
12 - 1/2	2,81	7,35	1,94	2,10	5,53
15 - 3/8	---	---	3,20	3,89	---
15 - 1/2	1,89	3,25	1,46	1,56	3,96
18 - 1/2	3,20	5,17	2,38	2,54	7,25
18 - 3/4	---	---	2,48	2,81	---
22 - 3/4	3,35	6,70	2,16	2,57	7,40
22 - 1"	---	---	3,96	---	---
28 - 3/4	7,41	11,49	4,92	5,67	---
28 - 1"	---	---	4,00	3,99	---
35 - 1 1/4	11,97	---	11,00	8,33	---
42 - 1 1/2	21,14	---	12,12	13,36	---
54 - 2"	40,02	---	22,55	22,79	---

- CONSULTAR EXISTENCIAS -